

## Ceiling Paint

<b>DESCRIPTION</b>	Full-matt low-odour waterborne acrylate latex paint for use on interior walls and ceilings. Offers excellent hiding power.
<b>EXAMPLES OF USE</b>	Plaster, concrete, brick, chipboard, wallpaper, and wood-fibre boards. Feelings Ceiling Paint can be used for repainting surfaces previously coated with waterborne or alkyd paints.
<b>TECHNICAL DATA</b>	Solids volume: approx. 35% Density: approx. 1.5 kg/l Scrub resistance: >1000 cycles (DIN 53778) Heat resistance: 85°C (ISO 3248) Finnish Emission Classification: M1
<b>Colour Range</b>	Available in white, most shades in the Feelings Interior Colour Range and pastel and mid – tone shades in the Tikkurila Symphony Colour Collection, BS 4800, RAL, NCS and most other colour ranges.
<b>SPECIFICATIONS</b>	
<b>Preparation</b>	Surfaces must be clean, dry, and free from grease, dirt, oil, wax, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes etc., and leveling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared. Spot prime all bare areas on previously painted surfaces with Feelings Ceiling Paint.
<b>APPLICATION</b>	Methods: brush, roller or spray application. For airless spray application use a 0.018" – 0.023" spray tip and thin by up to 5% with water. Thinning: if necessary thin by up to 5% with water.
<b>Painting Conditions</b>	All surfaces must be dry, the temperature of the air at least +5°C and the relative humidity of the air below 80%.
<b>Painting</b>	Stir the paint thoroughly and apply two coats of Feelings Ceiling Paint overall.
<b>Coverage</b>	7-10 m <sup>2</sup> /l per coat. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.
<b>Drying Times</b>	At 23°C and 50% relative humidity of the air: normally touch-dry after ½ hour and recoatable after 1-2 hours.

## Ceiling Paint

### Cleaning of Tools

Clean with water immediately after use.

### ENVIRONMENTAL

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

### HEALTH AND SAFETY CLASSIFICATION

EC Directive 88/397/EEC. Not classified as hazardous to health. Handle with care, avoid prolonged contact with skin and breathing of spray mist.

### STORAGE AND TRANSPORT

A Material Safety Data Sheet is available on request. Protect from Frost.

ADR/RID -

ome040604/723-s

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact: UK Distributors

Holman Specialist Paints Ltd  
1 Central Trading Estate  
Signal Way  
Swindon SN3 1PD

Tel 01793 511537 Fax 01793 431142

[www.feelingspaint.com](http://www.feelingspaint.com) e-mail [sales@feelingspaint.com](mailto:sales@feelingspaint.com)