

## Effect Paint

### DESCRIPTION

Full-matt low-odour waterborne translucent designer finish for use in interior rooms on surfaces which have been previously painted with Feelings Interior Paint. With a long 'open' time, Feelings Effect Paint can be used for colour washing, dragging, rag rolling, bagging, sponging etc.

### EXAMPLES OF USE

Interior walls and ceilings.

### TECHNICAL DATA

Solids volume: approx. 20%  
Density: approx. 1.1 kg/l  
Wash resistance: withstands wiping with a damp cloth  
Chemical resistance: Good (ISO 2812-1)  
Heat resistance: 85°C  
Base paints: CAP  
Classification of Finishing Materials: M1

### Colour Range

Available in the Feelings Interior Colour range and the complete Tikkurila Symphony Colour Collection. Also available in BS 4800, NCS, RAL and most other colour ranges.

The final colour of the Feelings Effect Paint will depend upon the colour of the Feelings Interior Paint used as the basecoat.

### SPECIFICATIONS

#### Preparation

Surfaces must be clean, dry, and free from grease, dirt, oil, wax, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes, etc., and leveling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared.

#### Priming

Prime unpainted and previously painted walls and ceilings with two coats of Feelings Interior Paint.

### APPLICATION

Methods: brush or roller application. Finishing with effect roller.  
Thinning: if necessary thin by up to 20% with water.

#### Painting Conditions

All surfaces to be painted must be dry, the temperature of the air between 15 and 23°C, and the relative humidity of the air between 30 and 70%.

#### Painting

Stir the paint thoroughly and apply one coat of Feelings Effect Paint evenly. Finish immediately by rolling over the surface, in one direction only, with a Feelings Effect Paint Roller, working in approximately 1 metre strips. Remove excess paint from the effect paint roller after each strip, by rolling onto a clean thick sheet of paper or cardboard. When a more translucent finish is required, thin the effect paint by up to 20% with water.

## Effect paint

<b>Coverage</b>	13-18 m <sup>2</sup> /l per coat. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture and porosity of the substrate.
<b>Drying Times</b>	At 23°C and 50% relative humidity of the air: normally touch-dry in 3 hours. Final hardness will be achieved in 14 days.
<b>Cleaning of Tools</b>	Clean with water immediately after use.
<b>ENVIRONMENTAL</b>	Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.
<b>HEALTH AND SAFETY CLASSIFICATION</b> according to EC Directive 99/45/EC	Not classified as hazardous to health. Handle with care, avoid prolonged contact with skin and breathing of spray mist.
<b>STORAGE AND TRANSPORT</b>	A Material Safety Data Sheet is available on request. Protect from Frost.  ADR/RID -

ome040604/722-s

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact:

**Holman Specialist Paints Ltd**  
**1 Central Trading Estate**  
**Signal Way**  
**Swindon SN3 1PD**  
 Tel 01793 511537      Fax 01793 431142  
[www.feelingspaint.com](http://www.feelingspaint.com)      e-mail sales@feelingspaint.com