

## Universal Primer

<b>DESCRIPTION</b>	Matt-finish low-odour waterborne acrylate latex primer for use on interior walls and ceilings. Offers a first-class foundation for subsequent coats of Feelings Extra Durable coating, Feelings Interior Paint and Feelings Ceiling Paint.
<b>EXAMPLES OF USE</b>	Plaster, concrete, brick, building block and boards, MDF, etc. Feelings Universal Primer can be used for repainting interior surfaces previously coated with waterborne, alkyd or acid catalysed paints.
<b>TECHNICAL DATA</b>	<p>Solids volume: approx. 33%</p> <p>Density: approx. 1.4 kg/l</p> <p>Scrub resistance: &gt;5000 cycles (DIN 53778)</p> <p>Chemical resistance: Good (ISO 2812-1)</p> <p>Heat resistance: 85°C (ISO 3248)</p> <p>Base paint: AP</p> <p>Classification of Finishing Materials: M1</p>
<b>Colour Range</b>	Available in white, most shades in the Feelings Interior Colour Range and pastel and mid - tone shades in the Tikkurila Symphony Colour Collection, BS 4800,RAL, NCS and most other colour ranges.
<b>SPECIFICATIONS</b> <b>Preparation</b>	Surfaces must be clean, dry, and free from grease, dirt, oil, wax, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes etc., and leveling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared.
<b>APPLICATION</b>	<p>Methods: brush, roller or spray application.</p> <p>Thinning: if necessary thin by up to 10% with water.</p>
<b>Painting Conditions</b>	All surfaces must be dry, the temperature of the air at least +5°C, and the relative humidity of the air below 80%.

## Universal Primer

### Painting

Stir the paint thoroughly. Prime unpainted wall and ceiling surfaces overall and spot prime all bare areas on previously painted walls and ceilings with Feelings Universal Primer

Prime absorbent surfaces with Feelings Universal Primer thinned by up to 10% with water, allow to dry and apply a further coat unthinned.

In areas of high humidity walls and ceilings should be primed with Feelings Moisture Stop prior to the application of Feelings Extra Durabl

### Coverage

7-10 m<sup>2</sup>/l per coat.

The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.

### Drying Times

At 23<sup>o</sup>C and 50% relative humidity of the air: normally touch-dry after ½ hour and recoatable after two hours.

### Cleaning of Tools

Clean with water immediately after use.

### ENVIRONMENTAL

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

### HEALTH AND SAFETY

#### CLASSIFICATION

according to EC Directive 99/45/EC

Not classified as hazardous to health.

Handle with care, avoid prolonged contact with skin and breathing of spray mist.

### STORAGE AND TRANSPORT

A Material Safety Data Sheet is available on request.  
Protect from Frost.

ADR/RID -

ome040604/726-s

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact:

Holman Specialist Paints Ltd  
1 Central Trading Estate  
Signal Way  
Swindon SN3 1PD

Tel 01793 511537 Fax 01793 431142

[www.feelingspaint.com](http://www.feelingspaint.com) e-mail sales@feelingspaint.com