

FILLER STOPPER (LAKKAKITTI)

DESCRIPTION	Quick drying alkyd filler for interior and exterior use which is easily sanded down.
EXAMPLES OF USE	For filling cracks, joints, nail holes, indentations, etc., on wood, building boards and metal surfaces. Filler Stopper can be used to fill bare, primed or painted surfaces.
Colour Range	White
SPECIFICATIONS Preparation	Surfaces must be clean, dry and free from dirt, oil, wax, rust, all loose material and surface contamination. Ensure that all glossy surfaces are thoroughly flatted down prior to filling. Better adhesion will be achieved by priming porous surfaces prior to filling.
Filling Conditions	The surface to be filled must be dry, the temperature of the air at least +5°C, and the relative humidity of the air at least 80%.
Filling	Apply with putty knife or spreader. On larger cracks, holes or defects some sinkage may occur and it may be necessary to apply a second application of Filler Stopper. When dry, Filler Stopper can be wet- or dry-sanded prior to priming or painting.
Drying Times	At 23°C and 50% relative humidity of the air: normally dry in ½ hour to 2 hours depending upon the layer thickness.
Cleaning of Tools	Remove excess filler from tools and clean with white spirit.
ENVIRONMENTAL	Avoid spillage into drains, water systems and soil. Empty cans should be recycled or disposed of in accordance with local regulations. Product waste should be destroyed according to the local regulations for hazardous waste.
TRANSPORT CLASSIFICATION	ADR/RID -

Iko/ome310304/ 0072270

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact:

Holman Specialist Paints Ltd
1 Central Trading Estate
Signal Way
Swindon SN3 1PD

Tel 01793 511537 FAX 01793 431142

www.holmanpaints.co.uk

e-mail sales@holmanpaints.co.uk