

KNOTTING LACQUER (VALTTI KNOTTING)

DESCRIPTION

Quick drying colourless solution containing special polymer for the treatment of knots and resinous areas on wooden surfaces. Knotting Lacquer will retard resin staining and seepage of resin gum from knots.

EXAMPLES OF USE

Knot and resinous areas on interior and exterior wooden surfaces prior to the application of paint coatings.

TECHNICAL DATA

Density: 0.8 kg/l

Colour Range

Colourless

SPECIFICATIONS

Preparation

Surfaces must be clean, dry and free from loose resin, dirt, oil, wax, all loose material and surface contamination. Treat exterior wooden surfaces with Valtti Base or an approved wood preservative prior to the application of Knotting Lacquer.

Note: Do not use Knotting Lacquer when treating timber with translucent wood finishes or wood stains.

Application

Methods: by brush

Painting Conditions

The surface to be treated must be dry, the temperature of the air at least +5°C, and the relative humidity of the air below 80%.

Painting

Apply two coats of Knotting Lacquer over all knots and resinous spots to an area no greater than a quarter of an inch larger than the size of each knot or resinous spot.

Drying Times

At 23°C and 50% relative humidity of the air: normally dry and recoatable after 15-30 minutes.

Cleaning of Tools

Clean brushes with Methylated Spirit immediately after use.

ENVIRONMENTAL

Avoid spillage into drains, water systems and soil. Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations for hazardous waste.

TRANSPORT CLASSIFICATION

ADR/RID 3 II

Iko/ome310304/ 0051940

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact:

Holman Specialist Paints Ltd

1 Central Trading Estate

Signal Way

Swindon SN3 1PD

Tel 01793 511537 FAX 01793 431142

www.holmanpaints.co.uk

e-mail sales@holmanpaints.co.uk