

MOULD REMOVAL

DESCRIPTION	Hypochlorite solution for the removal of mould and algae from both previously painted and unpainted surfaces.
PREPARATION	Remove dirt and all loose and flaking material.
METHODS OF APPLICATION	Sponge, brush or low pressure garden spray.
DIRECTIONS FOR USE	Mix Mould Removal Solution with water in the ratio of one part Mould Removal Solution to four parts water. To avoid possible streaks apply the mixture working from the bottom to the top of the area to be treated. Allow at least ½ an hour for the solution to react against the mould affected areas. For badly moulded surfaces apply the mixture wet-on-wet until the mould disappears. After treatment wash down all surfaces with clean water and allow to dry thoroughly. Note: When using Mould Removal Solution wear appropriate safety clothing i.e. gloves and eye protection in case of splashing.
Cleaning of Tools	Clean immediately after use with water.
PREVENT ENVIRONMENTAL DAMAGE	Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.
TRANSPORT	ADR/RID - Protect from frost.

lko/esi/ome180204/ 0061905

Manufacturer: TIKKURILA PAINTS OY, PO Box 53, 01301 VANTAA, FINLAND

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact:

Holman Specialist Paints Ltd
1 Central Trading Estate
Signal Way
Swindon SN3 1PD

Tel 01793 511537 FAX 01793 431142

www.holmanpaints.co.uk

e-mail sales@holmanpaints.co.uk