

VALTTI BASE

DESCRIPTION	Priming oil for use on exterior wood. Valtti Base is absorbed into the wood retarding the adverse effects of moisture and microbial growth.
EXAMPLES OF USE	Valtti Base is an ideal pre-treatment for bare exterior wood prior to the application of Valtti Wood Finishes and Tikkurila Paints.
TECHNICAL DATA	Solids Volume: 15% Density: 0.8 kg/l
Colour Range	Colourless and wood colour (337F). Valtti Base will not protect wood from the adverse effects of sunlight and therefore should be overcoated as soon as is possible.
SPECIFICATIONS Preparation	Surfaces must be clean, dry, and free from grease, dirt, oil, wax, all loose material and surface contamination. Use recommended Tikkurila products for mould removal and cleaning.
APPLICATION	Methods: brushing or dipping. Thinning: Valtti Base normally requires no thinning.
Painting Conditions	All surfaces to be painted must be dry, the moisture content of the wood below 20%, the temperature of the air at least +5°C, and the relative humidity of the air below 80%.
Painting	Stir thoroughly before and during use. Apply Valtti Base liberally overall, paying particular attention to end-grains, joints, cracks, etc. On very absorbent wood two coats of Valtti Base may be necessary. Protect plants from splashes of Valtti Base.
Coverage	Smooth wood: 8-10 m ² /litre per coat. Sawn wood: 4-5 m ² /litre per coat. Actual spreading rates will depend upon many factors including texture, porosity and moisture content of the substrate.
Drying Times	At 23°C and 50% relative humidity of the air: normally touch-dry in ½ hour and recoatable after 24 hours.
Cleaning of Tools	Clean immediately after use with white spirit.
PREVENT ENVIRONMENTAL DAMAGE	Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations. Note! Cleaning cloths or sanding dust containing the product can create fire by auto-ignition and should therefore be stored in water before disposal, or dried outdoors or incinerated immediately.

VALTTI BASE

TRANSPORT

ADR/RID 3 III

lko/esi/ome180204/ 0050500

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.

For further information or advice contact:

Holman Specialist Paints Ltd
1 Central Trading Estate
Signal Way
Swindon SN3 1PD
Tel 01793 511537 FAX 01793 431142
www.holmanpaints.co.uk e-mail sales@holmanpaints.co.uk