



VALTTI

Professional

EXTERIOR TRANSLUSCENT WOOD PROTECTION

Valtti Color Oil based matt semi-transparent penetrating wood finish for exterior use, available in a wide range of colours. Apply by brush or spray. Clean equipment with white spirit.

Maintenance: 3-5 years.
Spreading rate: Smooth wood 8-12m² /litre per coat Rough wood 4-8m² /litre per coat
Packaging: 20, 10, 3 & 1 litres

Valtti Satin Oil based durable satin semi-transparent wood finish for exterior use, available in a wide range of colours. Apply by brush or spray. Clean equipment with white spirit.

Maintenance: 3-5 years
Spreading rate: Smooth wood 10-14m² /litre per coat Rough wood 4-8m² /litre per coat
Packaging: 20, 10, 3 & 1 litres

Valtti Extra Oil based durable gloss semi-transparent wood finish for exterior use, available in a wide range of colours. Apply by brush or spray. Clean equipment with white spirit.

Maintenance: 3-5 years.
Spreading rate: Smooth wood 10-12m² / litre per coat Rough wood 4-8m² /litre per coat
Packaging: 20, 10, 3 & 1 litres

Valtti Akvacolor Waterborne matt semi-transparent penetrating wood finish for exterior use, available in a wide range of colours. Apply by brush or spray. Clean equipment with water.

Maintenance: 3-5 years
Spreading rate: Smooth wood 8-12m² /litre per coat Rough wood 4-8m² /litre per coat
Packaging: 10, 3 & 1 litres

Valtti Base Priming oil for exterior wood retarding the effects of moisture and microbial growth. Ideal pre-treatment prior to application of Valtti wood finishes and Tikkurila paints. Apply by brush or dipping. Clean equipment with white spirit.

Spreading rate: Smooth wood 8-10m² /litre Rough wood 4-5m² / litre
Packaging: 10, 3 & 1 litres

Unica Super Quick drying urethane alkyd lacquer for exterior and interior wood, with good abrasion resistance. Available in clear and a wide range of colours. Apply by brush or spray. Gloss, semi-gloss or semi-matt. Clean equipment with white spirit.

Spreading rate: Smooth wood 12-14m² /litre per coat
Packaging: 10, 3 & 1 litres

OPAQUE WOOD PROTECTION

Finngard Opaque (formerly Valtti Color Opaque) Waterborne durable semi-matt alkyd reinforced acrylate coating for exterior use available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush or spray. Clean equipment with water.

Maintenance: 5-7 years
Spreading rate: Smooth wood 8-10m² /litre per coat Rough wood 4-8m² /litre per coat
Packaging: 20, 10, 3 & 1 litres

Ultra Waterborne extended durability semi-matt pure acrylic coating for exterior use, available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush or spray. Clean equipment with water.

Maintenance: 8-10 years
Spreading rate: Smooth wood 8-10m² /litre per coat Rough wood 4-8m² /litre per coat
Packaging: 10, 3 & 1 litres

Valtti Teho Oil based durable semi-matt coating for exterior use, in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush or spray. Clean Equipment with white spirit.

Maintenance: 5 years
Spreading rate: Smooth wood 8-12m² /litre per coat Rough wood 4-8m² /litre per coat
Packaging: 10, 3 & 1 litres

EXTERIOR HIGH PERFORMANCE COATINGS

Miranol Universal oil based full gloss enamel paint for interior and exterior use with good impact and abrasion resistance. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush, roller or spray. Clean equipment with white spirit.

Spreading rate: Smooth wood 10-14m² /litre per coat
Packaging: 3 & 1 litres

Unica Semi-Gloss Enamel Universal special alkyd semi-gloss enamel paint for interior and exterior use on wood, metal, fibreglass and plastic substrates. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush, roller or spray. Clean equipment with white spirit.

Spreading rate: Smooth wood 10-12m² /litre per coat
Packaging: 10, 3 & 1 litres

Repco Maintenance Paint High performance semi-matt waterborne acrylate paint based on a special chemical and weather resistant resin for maintenance painting of PVC- plastisol and metal cladding. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush or spray. Clean equipment with water.

Maintenance: 10 years
Spreading rate: Smooth surfaces 8-10m² /litre per coat
Packaging: 10, 3 & 1 litres

HIGH PERFORMANCE MASONRY COATINGS

Finngard Opaque (formerly Valtti Color Opaque) Waterborne low maintenance semi-matt alkyd reinforced acrylic coating for exterior masonry facades available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush, roller or spray. Clean equipment with water.

Maintenance: 15 years
Spreading rate: Smooth 6-8m² /litre per coat Rough 3.5-5m² /litre per coat
Packaging: 20,10, 3 & 1 litres

Finngard Primer S (formerly Valtti Masonry Primer) Solvent borne clear acrylic primer, for use on exterior masonry facades prior to the application of Finngard Opaque. Apply by brush, roller or low pressure spray. Clean equipment with white spirit.

Spreading rate: Non-porous surface 5m² /litre Porous surface 0.5-2m² /litre
Packaging: 20 & 10 litres

Mould Removal Hypochlorite solution for the removal of mould and algae from previously painted and unpainted surfaces. Apply by sponge, brush or low pressure garden spray. Clean equipment with water.

Spreading rate: Dependent upon cleaning needs
Packaging: 5 & 1 litre

PRIMERS

Rostex Super Metal Primer (formerly Unica Metal Primer) Solvent borne quick drying anti-corrosive primer, for use on exterior and interior steel, galvanised metal, roughened aluminium, etc. Apply by brush or spray. Clean equipment with white spirit.

Spreading rate: Smooth surface 10-12m² /litre
Packaging: 10, 3 & 1 litres

Otex Adhesion Primer (formerly Unica Adhesion Primer) Full matt, quick drying solvent borne adhesion primer/undercoat, for use on exterior and interior wood, glass, tiles, PVC, aluminium, galvanised steel, etc. Available in a wide range of colours. Apply by brush, roller or spray. Clean equipment with white spirit.

Spreading rate: Smooth 8-10m² /litre
Packaging: 10, 3 & 1 litres

Luja Universal Primer Waterborne matt finish acrylate latex primer, for interior walls and ceilings. Offers a first class foundation for Luja finishing paints. Available in white and pastel colours. Apply by brush, roller or spray. Clean equipment with water.

Spreading rate: Smooth 7-10m² /litre
Packaging: 10, 3 & 1 litres

Helmi Primer Waterborne, matt finish acrylate primer for use on interior wood, panelling, doors, furniture, MDF, etc., prior to application of finish coats of Helmi. Available in a wide range of colours. Apply by brush, roller or spray. Clean equipment with water.

Spreading rate: 6-8m² /litre
Packaging: 10, 3 & 1 litre

INTERIOR PAINTS

Eko Joker Matt finish, solvent free co-polymer emulsion coating with European Eco label, for use on interior walls and ceilings with good resistance to abrasion and to washing. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush, roller or spray. Clean equipment with water.

Spreading rate: 10-12m² /litre per coat
Packaging: 10, 3 & 1 litres

Luja High performance extremely durable waterborne acrylate latex finishing paint, for use on interior walls and ceilings in humid areas e.g. bathrooms, kitchens, shower rooms, utility rooms, swimming pool areas, etc. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Semi-matt and semi-gloss finishes. Gives Class 0 fire rating on non-combustible surfaces. Apply by brush, roller or spray. Clean equipment with water.

Spreading rate: 7-10m² /litre per coat
Packaging: 10, 3 & 1 litres

Luja Moisture Stop Waterborne moisture stop material for improving the water resistance of walls and ceilings prior to the application of Luja finishing paint. Apply by brush, roller or spray. Clean equipment with water.

Spreading rate: 4-8m² /litre
Packaging: 10, 3 & 1 litres

Helmi Waterborne gloss or semi-matt acrylate, for use on interior wood, doors, panelling, furniture, walls, skirting, etc. which is hard wearing and easy to clean. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush, roller or spray. Clean equipment with water.

Spreading rate: 8-10m² /litre per coat
Packaging: 10, 3 & 1 litres

Empire Oil based thixotropic semi-matt finish for use on interior wood, doors, panelling, furniture, skirting, etc., which is very hard wearing and easy to clean. Available in white, the complete Tikkurila Professional and Façade Colour Collections, plus most of the British Standard, RAL and NCS Colour Ranges. Apply by brush, roller or spray. Clean equipment with white spirit.

Spreading rate: 10-13m² /litre per coat

Packaging: 3 & 1 litres

Akvacoat 100 Floor Paint Two component waterborne floor coating for painting new and previously painted floors subject to light mechanical stress and chemicals. Available in a wide range of colours. Apply by brush or roller. Clean equipment with water.

Spreading rate: Priming 5-7m² /litre Finishing 7-10m² /litre

Packaging: 10, 3 & 1 litres

INTERIOR WOOD COATINGS

Pirtti Waterborne, translucent quick drying matt wood stain for interior wood, available in a wide range of colours. Easily applied by brush, sponge or spray. Clean equipment with water. (For best results overcoat with Kiva Interior Lacquer, Kiva Floor Lacquer, or Unica Super Clear)

Spreading rate: 10-16m² /litre

Packaging: 10, 3 & 1 litres

Kiva Interior Lacquer Waterborne, non-yellowing acrylate lacquer for use on interior wood, tables, chairs, bookshelves, doors, toys, etc. Available in gloss, semi-gloss and semi-matt finishes in clear and a wide range of colours. Easily applied by brush, sponge or spray. Clean equipment with water.

Spreading rate: 8-14m² /litre per coat

Packaging: 10, 3 & 1 litre

Kiva Floor Primer (formerly Valtti Parquet Ace Priming Lacquer) Waterborne polyurethane-acrylate priming lacquer for use on bare interior wooden surfaces prior to the application of Kiva Floor Lacquer. Available in a wide range of colours. Apply by brush, mohair roller or spreader. Clean equipment with water.

Spreading rate: 10-12m² /litre per coat (roller application)

Packaging: 10, 3 & 1 litre

Kiva Floor Lacquer (formerly Valtti Parquet Ace Wood Lacquer) Waterborne polyurethane acrylate lacquer for use on interior wooden floors etc. Available in gloss and semi-gloss finishes in clear and a wide range of colours. Apply by brush, mohair roller or spreader. Clean equipment with water.

Spreading rate: 10-15m² /litre per coat

Packaging: 10, 3 & 1 litres

Unica Super Quick drying urethane lacquer for exterior and interior wooden windows, doors, floors, etc., with good abrasion resistance. Available in gloss, semi-gloss and semi-matt finishes in clear and a wide range of colours. Apply by brush or spray. Clean equipment with white spirit.

Spreading rate: 12-14m² /litre per coat

Packaging: 10, 3 & 1 litres

SUNDRIES

Knotting Lacquer Quick drying clear solution containing a special polymer for the treatment of knots and resinous areas in exterior wood.

Knotting Lacquer dries in 15-30 minutes.

Packaging: 3, 1 & 1/3 litres

Filler Stopper Quick drying white alkyd filler stopper for interior and exterior use which is easily sanded down. Can be used under waterborne, alkyd, oil based and acid catalyst paints.

Packaging: 1 & 1/3 litres

Cleaning Agent Alkaline waterborne cleaning and preparatory detergent for interior and exterior surfaces prior to painting.

Packaging: 3 & 1 litres

Roof Cleaning Agent Waterborne, cleaning and preparatory concentrate containing ammonia and emulsifying agent, for cleaning exterior sheet metal roofing and cladding. Roof Cleaning Agent is particularly suitable for cleaning zinc coated surfaces prior to painting.

Spreading rate 6-8m² /litre

Packaging: 3 & 1 litres (dilute 1 part with 4 parts water)

We also stock a wide range of thinners, paint and varnish removers, fillers, paint brushes, rollers, etc., as well as paints and lacquers for all types of substrates including fire retardant systems to Class O and Class 1. Please ask for details.

Holman Specialist Paints Ltd

1 Central Trading Estate, Signal Way, Swindon SN3 1PD

Tel: 01793 511537 Fax: 01793 431142

e-mail: sales@holmanpaints.co.uk

www.holmanpaints.co.uk